



DECLARATION OF PERFORMANCE

No

K003 v3

version: 1

1 Unique identification code of the product-type: **BW-20, 240x200x245**

2 Intended use/es: Agregate concrete masonry units

3 Manufacturer: Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP: System 4

5 Harmonised standard: EN 771-3:2011+A1:2015

Notified body/ies: not applicable

6 Declared performance/s:

Essential characteristics	Performances
Dimensions and dimensional tolerances: dimensions	240x200x245 mm
Dimensions and dimensional tolerances: dimensional tolerances	D1
Configuration: thickness of inner walls, tolerances	40 ± 2 mm
Compressive strength	≥ 3,5 N/mm ²
Dimensional stability	NPD
Bond strength: shear bond strength	0,15 N/mm ²
Bond strength: flexural bond strength	NPD
Reaction to fire	A1
Water absorption	not to be left exposed
Water vapour permeability	NPD
Direct airborne sound insulation: gross density	1300 ± 130 kg/m ³
Direct airborne sound insulation: configuration: thickness of inner walls, tolerances	40 ± 2
Direct airborne sound insulation: dimensions	240x200x245 mm
Direct airborne sound insulation: tolerances	+3/-5 mm
Thermal resistance	NPD
Durability against freeze/thaw	NPD
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 9th June 2017

GRZEGORZ HESE
DYREKTOR
DS. TECHNICZNO PRODUKCYJNYCH

Grzegorz Hese