

DECLARATION OF PERFORMANCE
FEL'X MULTI EN 1.25 M BLUE PL / EN 13859-1 / v 1.4

1. Unique identification code of the product-type :	FEL'X MULTI EN 1.25 M BLUE PL
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :	FEL'X MULTI EN 1.25 M BLUE PL Production date : see product or packaging.
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :	Sarking and underlays for roofing
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :	ICOPAL S.A.S. / Siplast 12, rue de la Renaissance F- 92184 ANTONY Cedex
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) :	-
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V :	3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :	CSTB, notified body n° 0679 LNE, notified body n° 0071 has(have) carried out the determination of the product type on the basis of type-testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :	-

9. Declared performance :

Harmonised technical specifications				
EN 13859-1 : 2010				
Essential characteristics	Performance	Units	Recording of results	Standards
Reaction to fire	E	--	--	EN 13501-1
Watertightness	W1	--	--	EN 1928
Tensile strength LxW	330 x 270	N/50 mm	-10 %	EN 12311-1
Elongation LxW	50 x 58	%	-20 %	EN 12311-1
Resistance to tearing L x W	300 x 250	N	-10 %	EN 12310-1
Flexibility at low temperature	-20	°C	MLV	EN 1109
EN 13859-1/C Durability : Resistance to water penetration	W1	--	--	EN 1928
EN 13859-1/C Durability : Tensile strength L x W	200 x 200	N/50 mm	-10 %	EN 12311-1
EN 13859-1/C Durability : Elongation L x W	20 x 20	%	-20 %	EN 12311-1

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

Antony, 24/09/2013

Alain Blotière
Technical Director

