

No P151

1 Unique identification code of the product-type: **W/PET PLUS - SBS/ICOPAL**

2 Intended use/es: Roof waterproofing

3 Manufacturer: BMI Icopal Sp. z o.o., ul. Łaska 169/197,
98–220 Zduńska Wola, Polska (PL)

4 System/s of AVCP: System 2+, System 4

5 Harmonised standard: EN 13707:2004+A2:2009

Notified body/ies: The notified factory production control certification body No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+)


6 Declared performance/s:

| Essential characteristics | Performances |
|------------------------------|--|
| External fire performance | NPD |
| Reaction to fire | NPD |
| Watertightness | Watertight at 10 kPa (method A) |
| Tensile properties | 450 ± 150 N/50 mm (tensile strength longitudinal) |
| | 350 ± 150 N/50 mm (tensile strength transverse) |
| | 30 ± 15 % (elongation longitudinal) |
| | 35 ± 15 % (elongation transverse) |
| Root resistance | NPD |
| Resistance to static loading | NPD |
| Resistance to impact | NPD |
| Tear resistance | 250 ± 100 N (nail shank, longitudinal) |
| | 250 ± 100 N (nail shank, transverse) |
| Joint strength | NPD (peel resistance of joints) |
| | NPD (shear resistance of joints) |
| Durability | 115 ± 15 °C (heat flow after heat oven exposure) |
| Pliability | -10 °C (flexibility at low temperature) |
| Dangerous substances | Not contain |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 25th May 2020


Grzegorz Hese
 Dyrektor Zakładów
 Produkcji BMI Icopal