



DECLARATION OF PERFORMANCE

No

P006-4

version: 1

1 Unique identification code of the product-type:

I/333 (A-330)

2 Intended use/es:

damp proofing for buildings

3 Manufacturer:

Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:

System 2+, System 4

5 Harmonised standard:

EN 13969:2004+A1:2006

Notified body/ies:

The notified factory production control certification body No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+)

6 Declared performance/s:

Essential characteristics	Performances
Reaction to fire	NPD
Watertightness	2 kPa
Resistance to impact, method A	NPD
Resistance to impact, method B	NPD
Shear resistance of joints, side lap	250 ± 100 N/50 mm
Shear resistance of joints, end lap	350 ± 100 N/50 mm
Flexibility at low temperatures (pliability)	0 °C
Tensile strength longitudinal	500 ± 150 N/50 mm
Tensile strength transverse	300 ± 100 N/50 mm
Elongation longitudinal	3 ± 2 %
Elongation transverse	3 ± 2 %
Resistance to static load, method B	NPD
Resistance to tearing longitudinal	70 ± 30 N
Resistance to tearing transverse	70 ± 30 N
Durability against artificial ageing/degradation: watertightness	2 kPa
Durability against chemicals: watertightness	NPD
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 11h February 2019

GRZEGORZ HESSE
OS. TECHNICZNE PRODUKCYJNYCH
Grzegorz Hesse