



DECLARATION OF PERFORMANCE

No

P041-3

version: 1

1 Unique identification code of the product-type:

W/64

2 Intended use/es:

- a. roof waterproofing
- b. roof waterproofing subject to reaction to fire

3 Manufacturer:

Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:

System 2+, System 3

5 Harmonised standard:

EN 13707:2004+A2:2009

Notified body/ies:

The notified factory production control certification body No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+, scope of application a.)

The notified testing laboratory No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 3, scope of application b.)

6 Declared performance/s:

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Class E
Watertightness	10 kPa
Tensile strength longitudinal	450 ± 150 N/50 mm
Tensile strength transverse	250 ± 100 N/50 mm
Elongation longitudinal	3 ± 2 %
Elongation transverse	3 ± 2 %
Root resistance	NPD
Resistance to static load, method A	NPD
Resistance to impact, method A	NPD
Resistance to tearing	NPD
Peel resistance of joints	NPD
Shear resistance of joints	NPD
Durability: heat flow after heat oven exposure	100 ± 10 °C
Flexibility at low temperatures (pliability)	5 °C
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

CZŁONEK ZARZĄDU
DYREKTOR
DS. TECHNICZNO PRODUKCYJNYCH
Grzegorz Hase

At Zduńska Wola on 11th February 2019