



# DECLARATION OF PERFORMANCE

No

P121-1

version: 1

1 Unique identification code of the product-type:

VILLAS P/64

2 Intended use/es:

roof waterproofing

3 Manufacturer:

Icopal Sp. z o.o., ul. Łaska 169/197,  
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:

System 2+, System 4

5 Harmonised standard:

EN 13707:2004+A2:2009

Notified body/ies:

The notified factory production control certification body No. 1434:  
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.  
(system 2+)

6 Declared performance/s:


Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	NPD
Watertightness	10 kPa
Tensile strength longitudinal	550 ± 150 N/50 mm
Tensile strength transverse	250 ± 100 N/50 mm
Elongation longitudinal	3 ± 2 %
Elongation transverse	3 ± 2 %
Root resistance	NPD
Resistance to static load, method A	NPD
Resistance to impact, method A	NPD
Resistance to tearing	NPD
Peel resistance of joints	NPD
Shear resistance of joints	NPD
Durability: heat flow after heat oven exposure	NPD
Durability: flexibility at low temperature after heat oven exposure	NPD
Flexibility at low temperatures (pliability)	5 °C
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 11th February 2019

  
 CZŁONK ZARZĄDU  
 D. TECHNICZNE PRODUKCYJNYCH  
 STANISŁAW HOSE