

DECLARATION OF PERFORMANCE

No

P154

1 Unique identification code of the product-type:

GLASBIT G200 S40-15 SZYBKI PROFIL SBS

Intended use/es:

a. damp proofing for buildings, including basement tanking

b. damp proofing for buildings, including basement tanking

subject to reaction to fire

Manufacturer:

BMI Icopal Sp. z o.o., ul. Łaska 169/197,

98–220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:

System 2+, System 3

5 Harmonised standard:

Notified body/ies:

EN 13969:2004, EN 13969:2004/A1:2006

The notified factory production control certification body No. 1434:

POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.

(system 2+, scope of application a.)

The notified testing laboratory No. 1434:

POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.

(system 3, scope of application b.)

6 Declared performance/s:

Essential characteristics	Performances
Reaction to fire	Class E
Watertightness, method B	Watertight at 60 kPa
Resistance to impact, method A	2000 mm
Resistance to impact, method B	NPD
Shear resistance of joints, side lap	1500 ± 1000 N/50 mm
Shear resistance of joints, end lap	1500 ± 1000 N/50 mm
Flexibility at low temperatures (pliability)	-15°C
Tensile strength longitudinal	1500 ± 500 N/50 mm
Tensile strength transverse	2500 ± 700 N/50 mm
Elongation longitudinal	8 ± 5 %
Elongation transverse	8 ± 5 %
Resistance to static load, method B	10 kg
Resistance to tearing longitudinal	500 ± 250 N/50 mm
Resistance to tearing transverse	250 ± 100 N/50 mm
Durability against artificial ageing/degradation: watertightness	Watertight at 60 kPa
Durability against chemicals: watertightness	NPD

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 17th August 2021

Dyrektor Zakladów Produkcji BM Icopal