

No **P054-6**

**1 Unique identification code of the product-type:** **Fundament 4,0 Szybki Profil SBS**

**2 Intended use/es:** damp proofing for buildings, including basement tanking

**3 Manufacturer:** BMI Icopal Sp. z o.o., ul. Łaska 169/197,  
98–220 Zduńska Wola, Polska (PL)

**4 System/s of AVCP:** System 2+, System 4

**5 Harmonised standard:** EN 13969:2004+A1:2006

**Notified body/ies:** The notified factory production control certification body No. 1488:  
INSTYTUT TECHNIKI BUDOWLANEJ  
(system 2+)

**6 Declared performance/s:**


Essential characteristics	Performances
Reaction to fire	NPD
Watertightness	200 kPa
Resistance to impact, method A	1500 mm
Resistance to impact, method B	2000 mm
Shear resistance of joints, side lap	800 +200/-100 N/50 mm
Shear resistance of joints, end lap	1000 +200/-100 N/50 mm
Flexibility at low temperatures (pliability)	-12 °C
Tensile strength longitudinal	950 +350/-0 N/50 mm
Tensile strength transverse	750 +350/-0 N/50 mm
Elongation longitudinal	50 ± 15 %
Elongation transverse	50 ± 15 %
Resistance to static load, method B	20 kg
Resistance to tearing longitudinal	350 ± 100 N
Resistance to tearing transverse	350 ± 100 N
Durability against artificial ageing/degradation: watertightness	200 kPa
Durability against chemicals: watertightness	NPD
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 4th March 2020

  
**CZŁONEK ZARZĄDU**  
**DYREKTOR**  
**DS. TECHNICZNO-PRODUKCYJNYCH**  
*Grzegorz Hese*