

No **P122-2**

1 Unique identification code of the product-type: **VILLAS STANDARD P-PYE PV250 S40**

2 Intended use/es:

- a. roof waterproofing
- b. roof waterproofing subject to reaction to fire

3 Manufacturer:

BMI Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:

System 2+, System 3

5 Harmonised standard:

EN 13707:2004+A2:2009

Notified body/ies:

The notified factory production control certification body No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+, scope of application a.)

The notified testing laboratory No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 3, scope of application b.)

6 Declared performance/s:

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Class E
Watertightness	Watertight
Tensile strength longitudinal	1000 ± 200 N/50 mm
Tensile strength transverse	700 ± 200 N/50 mm
Elongation longitudinal	8 ± 5 %
Elongation transverse	8 ± 5 %
Root resistance	NPD
Resistance to static load, method B	20 kg
Resistance to impact, method A	1250 mm
Resistance to impact, method B	NPD
Resistance to tearing longitudinal	250 ± 100 N/50 mm
Resistance to tearing transverse	250 ± 100 N/50 mm
Peel resistance of joints	NPD
Shear resistance of joints, side lap	700 ± 200 N/50 mm
Shear resistance of joints, end lap	1000 ± 200 N/50 mm
Durability: heat flow after heat oven exposure	NPD
Durability: flexibility at low temperature after heat oven exposure	NPD
Flexibility at low temperatures (pliability)	0 °C
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 20th February 2020

**CZŁONEK ZARZĄDU
DYREKTOR
DS. TECHNICZNO PRODUKCYJNYCH**

Grzegorz Hese