

No P123-2

**1 Unique identification code of the product-type:** **VILLAS STANDARD P-PYE PV250 S40 - Typ T**

**2 Intended use/es:**

- a. damp proofing for buildings, including basement tanking
- b. damp proofing for buildings, including basement tanking subject to reaction to fire

**3 Manufacturer:**

BMI Icopal Sp. z o.o., ul. Łaska 169/197,  
98-220 Zduńska Wola, Polska (PL)

**4 System/s of AVCP:**

System 2+, System 3

**5 Harmonised standard:**

EN 13969:2004 + EN 13969:2004/A1:2006

**Notified body/ies:**

The notified factory production control certification body No. 1434:  
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.  
(system 2+, scope of application a.)

The notified testing laboratory No. 1434:  
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.  
(system 3, scope of application b.)

**6 Declared performance/s:**

Essential characteristics	Performances
Reaction to fire	Class E
Watertightness	Watertight
Resistance to impact, method A	1250 mm
Resistance to impact, method B	NPD
Shear resistance of joints, side lap	700 ± 200 N/50mm
Shear resistance of joints, end lap	1000 ± 200 N/50mm
Flexibility at low temperatures (pliability)	0 °C
Tensile strength longitudinal	1000 ± 200 N/50mm
Tensile strength transverse	700 ± 200 N/50mm
Elongation longitudinal	8 ± 5 %
Elongation transverse	8 ± 5 %
Resistance to static load, method B	20 kg
Resistance to tearing longitudinal	250 ± 100 N
Resistance to tearing transverse	250 ± 100 N
Durability against artificial ageing/degradation: watertightness	Watertight
Durability against chemicals: watertightness	NPD
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 20th February 2020

**CZŁONEK ZARZĄDU  
DYREKTOR  
DS. TECHNICZNO PRODUKCYJNYCH**

*Grzegorz Hese*