

No **P124-2**

1 Unique identification code of the product-type: **VILLAS STANDARD W-PYE PV250 S52H**

2 Intended use/es:
 a. roof waterproofing
 b. roof waterproofing subject to reaction to fire

3 Manufacturer: BMI Icopal Sp. z o.o., ul. Łaska 169/197,
 98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP: System 2+, System 3

5 Harmonised standard: EN13707:2004+A2:2009

Notified body/ies:

The notified factory production control certification body No. 1434:
 POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
 (system 2+, scope of application a.)

The notified testing laboratory No. 1434:
 POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
 (system 3, scope of application b.)

6 Declared performance/s:

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Class E
Watertightness, method A	Watertight
Tensile strength longitudinal	1000 ± 200 N/50 mm
Tensile strength transverse	700 ± 200 N/50 mm
Elongation longitudinal	8 ± 5 %
Elongation transverse	8 ± 5 %
Root resistance	NPD
Resistance to static load, method A	20 kg
Resistance to impact, method A	1250 mm
Resistance to tearing	NPD
Peel resistance of joints	NPD
Shear resistance of joints, side lap	700 ± 200 N/50 mm
Shear resistance of joints, end lap	1000 ± 200 N/50 mm
Durability: heat flow after heat oven exposure	100 ± 10 °C
Flexibility at low temperatures (pliability)	0 °C
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 20th February 2020


CZŁONEK ZARZĄDU
DYREKTOR
DS. TECHNICZNO PRODUKCYJNYCH
Grzegorz Hese