



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name

**Siplast Klej Szybki Styk SBS**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Adhesive.  
To be used cool. For outdoor use.  
Bonding of thermal insulation boards, asphalt roof coverages and bituminous shingles.  
For waterproof coatings.

Uses advised against

not determined

#### 1.3 Details of the supplier of the safety data sheet

Icopal Sp. z o.o.  
ul. Łaska 169/197  
98-220 Zduńska Wola  
Poland

Telephone: +48 / 043 823 41 11  
e-mail: kch.pl@icopal.com  
Website: www.icopal.pl

#### 1.4 Emergency telephone number

Emergency information service

National Poisons Information Service (NPIS): For medical advice or information you should contact your GP or NHS 111 (or NHS 24 in Scotland) on 111 (for 24 hour health advice)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard state-ment
2.6	flammable liquid	Cat. 3	(Flam. Liq. 3)	H226
3.4S	skin sensitisation	Cat. 1	(Skin Sens. 1)	H317

#### Remarks

For full text of H-phrases: see SECTION 16.

#### Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

#### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008 (CLP)

##### Signal word

Warning

##### Pictograms

GHS02, GHS07



#### Hazard statements

H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.

#### Precautionary statements

##### Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist/vapours.  
P280 Wear protective gloves/protective clothing.

##### Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water/shower.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

##### Precautionary statements - disposal

P501 Dispose of contents / container to an approved waste disposal.

#### Additional labelling requirements

EUH066 Repeated exposure may cause skin dryness or cracking.

**Hazardous ingredients for labelling:** Pitch, petroleum, arom., chinesis gum rosin

### 2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Name of substance	Identifier	wt%	Classification acc. to 1272/2008/EC	Notes
Asphalt, oxidized	CAS No 64742-93-4  EC No 265-196-4  REACH Reg. No 01-2119498270-36-xxxx	50 – < 75	not classified	OEL
N-butyl acetate	CAS No 123-86-4  EC No 204-658-1  REACH Reg. No 01-2119485493-29-xxxx	10 – < 25	Flam. Liq. 3 / H226 STOT SE 3 / H336	OEL



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

Name of substance	Identifier	wt%	Classification acc. to 1272/2008/EC	Notes
chinese gum rosin	CAS No 8050-09-7  EC No 232-475-7  Index No 650-015-00-7	1 - < 5	Skin Sens. 1 / H317	
Pitch, petroleum, arom.	CAS No 68187-58-6  EC No 269-110-6  REACH Reg. No 01-2119539471-40-xxxx	1 - < 5	Skin Sens. 1 / H317 Carc. 1B / H350	*
Amides, tallow, hydrogenated, N-[(dimethylamino)propyl]	CAS No 69013-24-7  EC No 273-783-1	1 - < 5	Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Aquatic Acute 1 / H400	

### Notes

\*: Content of PAH = 1,37%  
OEL: Substance with a national occupational exposure limit value

For full text of abbreviations: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Take off contaminated clothing. Remove the residues of the product with liquid paraffin or edible oil. Wash skin with water and soap or mild detergent. Remove contaminated/soaked clothes to safe place away from heat and sources of ignition.

#### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Conscious victim can drink 100-200 ml of liquid paraffin. Do not give milk or edible oils to drink. Do NOT induce vomiting. In case of spontaneous vomiting the victim should lean forward to prevent aspiration. Seek medical advice immediately.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### 4.2 Most important symptoms and effects, both acute and delayed

Description of known symptoms following exposure, if relevant - see section 11.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

water spray, water mist, foam, fire extinguishing powder, carbon dioxide (CO<sub>2</sub>), sand

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Flammable. Do not use water jets - the risk of splash. Closed containers exposed to fire or high temperature can explode due to increased pressure inside. Cool closed containers exposed to fire with water spray. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Hot product may adhere to skin or clothes.

#### Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), fumes

### 5.3 Advice for firefighters

Fire fighting crew should be adequately trained and equipped with self-contained breathing apparatus and full protective clothing. Fight fire with normal precautions from a reasonable distance. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Do not breathe vapours. Wear protective clothing. The solvent contained in the mixture evaporates easily -ensure adequate ventilation. Eliminate all sources of ignition. Vapors of the solvent are heavier than air, they can form an explosive mixture with air. Vapors may spread along the floor and reach distant ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Collect contaminated soil and dispose of it.

### 6.3 Methods and material for containment and cleaning up

#### Advices on how to contain a spill

Bunding. Covering of drains.

#### Advices on how to clean up a spill

Do not flush with water. Cover with non-combustible absorbent material. (kieselgur (diatomite), sand, vermiculite, universal binder). Collect to labelled, closed waste container and remove for disposal.

#### Appropriate containment techniques

Use of adsorbent materials.

#### Other information relating to spills and releases

Ventilate affected area.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

#### • Measures to prevent fire as well as aerosol and dust generation

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only non-sparking tools.

#### • Warning

Vapours may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Protect from sunlight.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure easy access to fire fighting measures in the place of use and storage.

### 7.3 Specific end use(s)

Data are not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
GB	butyl acetate	123-86-4	WEL	150	724	200	966	EH40/2005
GB	rosin-based solder flux fume	8050-09-7	WEL		0.05		0.15	EH40/2005
GB	asphalt (petroleum)	8052-42-4	WEL				10	EH40/2005

#### Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### Relevant DNELs/DMELs/PNECs and other threshold levels

#### • relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Asphalt, oxidized	64742-93-4	DNEL	2.9 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
N-butyl acetate	123-86-4	DNEL	300 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
N-butyl acetate	123-86-4	DNEL	300 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
N-butyl acetate	123-86-4	DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
N-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

#### • relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
N-butyl acetate	123-86-4	PNEC	0.18 mg/l	aquatic organisms	freshwater	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.018 mg/l	aquatic organisms	marine water	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	35.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.981 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.098 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.09 mg/kg	terrestrial organisms	soil	short-term (single instance)
Pitch, petroleum, arom.	68187-58-6	PNEC	3.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Pitch, petroleum, arom.	68187-58-6	PNEC	0.291 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Pitch, petroleum, arom.	68187-58-6	PNEC	0.128 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Pitch, petroleum, arom.	68187-58-6	PNEC	3.64 µg/kg	terrestrial organisms	soil	short-term (single instance)



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

if there is a risk of splash wear eye/face protection.

##### Skin protection

- hand protection

Wear suitable gloves. Protective gloves should be replaced immediately if damaged or in case of signs of wear.

- type of material

IIR: isobutene-isoprene (butyl) rubber, Nitrile, Neoprene

- other protection measures

Use protective clothing. Wash hands thoroughly after handling. Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

##### Respiratory protection

Not required in normal conditions. In case of inadequate ventilation wear respiratory protection. Full face mask/half mask/quarter mask (EN 136/140). Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

##### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid (paste)
Colour	black
Odour	weak, characteristic for organics

#### Other physical and chemical parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>130 °C
Flash point	>31 °C (closed cup)
Evaporation rate	not determined
Flammability (solid, gas)	not relevant
Explosive limits	
• lower explosion limit (LEL)	1.2 vol%
• upper explosion limit (UEL)	15 vol%
Vapour pressure	10.15 hPa at 18.49 °C
Density	not determined
Relative density	1.15 at 20 °C (water = 1)
Solubility(ies)	Petroleum solvents
Water solubility	insoluble



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

Partition coefficient	
n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none (not one)
Oxidising properties	none (not one)

### 9.2 Other information

Data are lacking.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is not reactive under normal ambient conditions.

#### • if heated

risk of ignition

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

strong oxidisers - strong bases - strong acids

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Shall not be classified as acutely toxic.

##### • Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Asphalt, oxidized	64742-93-4	oral	LD50	>5,000 mg/kg	rat
Asphalt, oxidized	64742-93-4	dermal	LD50	>2,000 mg/kg	rabbit
Asphalt, oxidized	64742-93-4	inhalation: vapour	LC50	>94.4 mg/m <sup>3</sup> /4h	rat
N-butyl acetate	123-86-4	oral	LD50	10,760 mg/kg	rat





# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
N-butyl acetate	123-86-4	inhalation: dust/mist	LC50	>23.4 mg/l/4h	rat
N-butyl acetate	123-86-4	dermal	LD50	>14,000 mg/kg	not specified
chinese gum rosin	8050-09-7	oral	LD50	>2,000 mg/kg	rat
Pitch, petroleum, arom.	68187-58-6	oral	LD50	>15,000 mg/kg	rat
Pitch, petroleum, arom.	68187-58-6	dermal	LD50	>2,000 mg/kg	rat
Amides, tallow, hydrogenated, N-[(di-methylamino)propyl]	69013-24-7	oral	LD50	>2,000 mg/kg	rat

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitisation

May cause an allergic skin reaction.

### Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

### Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

abdominal pain, nausea

#### • If in eyes

if splashed into an eye it may cause mechanical irritation of the cornea, conjunctival suffusion

#### • If inhaled

In case of prolonged exposure narcotic effects are possible: headache, vertigo, nausea, narcosis, deficits in perception and coordination, reaction time, or sleepiness, loss of consciousness.

#### • If on skin

localised redness, scaling, allergic reactions, has degreasing effect on the skin, repeated exposure may cause skin dryness or cracking

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### SECTION 12: Ecological information

#### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

##### Aquatic toxicity (acute)

Test data are not available for the complete mixture.

##### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Asphalt, oxidized	64742-93-4	LL50	>1,000 mg/l	rainbow trout	96 h
Asphalt, oxidized	64742-93-4	EL50	>1,000 mg/l	algae	72 h
N-butyl acetate	123-86-4	LC50	18 mg/l	fish	96 h
N-butyl acetate	123-86-4	EC50	44 mg/l	aquatic invertebrates	48 h
N-butyl acetate	123-86-4	ErC50	392 mg/l	algae	48 h
chinese gum rosin	8050-09-7	LC50	1.7 mg/l	fish	96 h
chinese gum rosin	8050-09-7	EL50	>1,000 mg/l	fish	96 h
chinese gum rosin	8050-09-7	LL50	<10 mg/l	fish	96 h
chinese gum rosin	8050-09-7	ErC50	39.6 mg/l	algae	72 h
Pitch, petroleum, arom.	68187-58-6	LL50	128 mg/l	fish	96 h
Pitch, petroleum, arom.	68187-58-6	EL50	>1,000 mg/l	aquatic invertebrates	48 h
Amides, tallow, hydrogenated, N-[(dimethylamino)propyl]	69013-24-7	EbC50	0.34 mg/l	algae	48 h

##### Aquatic toxicity (chronic)

##### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Asphalt, oxidized	64742-93-4	NOAEL	>1,000 mg/l	daphnia magna	21 d
Asphalt, oxidized	64742-93-4	NOAEL	>1,000 mg/l	rainbow trout	28 d
N-butyl acetate	123-86-4	EC50	34.2 mg/l	aquatic invertebrates	21 d
N-butyl acetate	123-86-4	LC50	43.5 mg/l	aquatic invertebrates	21 d
N-butyl acetate	123-86-4	ErC50	335 mg/l	algae	24 h
N-butyl acetate	123-86-4	NOEC	23.2 mg/l	aquatic invertebrates	21 d
N-butyl acetate	123-86-4	LOEC	47.6 mg/l	aquatic invertebrates	21 d
chinese gum rosin	8050-09-7	EC50	>10,000 mg/l	microorganisms	3 h
Pitch, petroleum, arom.	68187-58-6	LC50	5.6 µg/l	fish	64 h



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Pitch, petroleum, arom.	68187-58-6	EC50	59.7 µg/l	aquatic invertebrates	24 h
Pitch, petroleum, arom.	68187-58-6	NOEC	4 µg/l	fish	42 d
Pitch, petroleum, arom.	68187-58-6	NOELR	100 mg/l	aquatic invertebrates	21 d

### Biodegradation

n-butyl acetate: the substance is readily biodegradable  
Asphalt: no data available - UVCB substance

### 12.2 Persistence and degradability

#### Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time	Notes
Asphalt, oxidized	64742-93-4	biotic/abiotic		d	hydrolysis - not relevant, photolysis - not relevant
N-butyl acetate	123-86-4	biotic/abiotic	83 %	28 d	

### 12.3 Bioaccumulative potential

Data are not available.

#### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW
N-butyl acetate	123-86-4	15.3	2.3 (pH value: 7, 25 °C)
chinese gum rosin	8050-09-7		3.01 (20 °C)
Pitch, petroleum, arom.	68187-58-6		4.43 - 6.47 (25 °C)

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Other adverse effects

Data are not available.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Waste treatment-relevant information

Do not store at landfill sites. Recommended way of disposal: incineration in special waste incinerators.

##### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

##### Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

##### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

14.1	UN number	1139
14.2	UN proper shipping name	COATING SOLUTION
14.3	Transport hazard class(es) Class	3 (flammable liquids)
14.4	Packing group	III (substance presenting low danger)
14.5	Environmental hazards	none (not one) (non-environmentally hazardous acc. to the dangerous goods regulations)
14.6	Special precautions for user	Provisions for dangerous goods (ADR) should be complied within the premises.
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

##### • Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1139
Proper shipping name	COATING SOLUTION
Class	3
Classification code	F1
Packing group	III
Danger label(s)	3



Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E
Hazard identification No	30
<b>Emergency Action Code</b>	<b>3YE</b>

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### Remarks

The product meets the requirements set up in 2.2.3.1.5 of ADR and RID agreements in terms of physicochemical properties and therefore, if packed in receptacles of not more than 450 litre capacity, are not a subject to ADR or RID.

#### • International Maritime Dangerous Goods Code (IMDG)

UN number	1139
Proper shipping name	COATING SOLUTION
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A

#### • International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	1139
Proper shipping name	Coating solution
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

##### • Restrictions according to REACH, Annex XVII

Polycyclic Aromatic Hydrocarbons (concentration = 0,023%).

##### • List of substances subject to authorisation (REACH, Annex XIV)

None of the ingredients are listed.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

### • SVHC substances included in the Candidate List according to article 59 p. 10 of REACH

Benzo[a]pyrene (concentration = 6,97 ppm).

N,N-dimethylacetamide (concentration below 13,25 ppm).

### • Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)

VOC content 109,6 g/l

## 15.2 Chemical Safety Assessment

The Chemical Safety Assessment is not required for the mixture.

## SECTION 16: Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
BCF	Bioconcentration factor
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
log KOW	n-Octanol/water



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

Abbr.	Descriptions of used abbreviations
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

### Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H400	Very toxic to aquatic life.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

## Siplast Klej Szybki Styk SBS

Version number: GHS 1.0

Date of compilation: 2018-02-21

---

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.