

No **P006-6**

**1 Unique identification code of the product-type:** **I/333 ( A-330 )**

**2 Intended use/es:** damp proofing for buildings

**3 Manufacturer:** BMI Icopal Sp. z o.o., ul. Łaska 169/197,  
98–220 Zduńska Wola, Polska (PL)

**4 System/s of AVCP:** System 2+, System 4

**5 Harmonised standard:** EN 13969:2004+A1:2006

**Notified body/ies:** The notified factory production control certification body No. 1434:  
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.  
(system 2+)

**6 Declared performance/s:**


Essential characteristics	Performances
Reaction to fire	NPD
Watertightness, method A	Watertight
Resistance to impact, method A	NPD
Resistance to impact, method B	NPD
Shear resistance of joints, side lap	250 ± 100 N/50 mm
Shear resistance of joints, end lap	350 ± 100 N/50 mm
Flexibility at low temperatures (pliability)	0 °C
Tensile strength longitudinal	500 ± 150 N/50 mm
Tensile strength transverse	300 ± 100 N/50 mm
Elongation longitudinal	3 ± 2 %
Elongation transverse	3 ± 2 %
Resistance to static load, method B	NPD
Resistance to tearing longitudinal	70 ± 40 N
Resistance to tearing transverse	70 ± 40 N
Durability against artificial ageing/degradation: watertightness, method A	Watertight
Durability against chemicals: watertightness	NPD
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 20th February 2020

  
**CZŁONEK ZARZĄDU**  
**DYREKTOR**  
**DS. TECHNICZNO PRODUKCYJNYCH**  
 Grzegorz Hase