

No **P013-7**

<b>1 Unique identification code of the product-type:</b>	<b>PLASTER P-180/2000</b>
<b>2 Intended use/es:</b>	a. roof waterproofing b. roof waterproofing subject to reaction to fire
<b>3 Manufacturer:</b>	BMI Icopal Sp. z o.o., ul. Łaska 169/197, 98-220 Zduńska Wola, Polska (PL)
<b>4 System/s of AVCP:</b>	System 2+, System 3
<b>5 Harmonised standard:</b>	EN 13707:2004+A2:2009
<b>Notified body/ies:</b>	POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.; No. 1434 (system 2+, scope of application a.)  INSTYTUT TECHNIKI BUDOWLANEJ; No. 1488 (system 3, scope of application b.)
<b>6 Declared performance/s:</b>	

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Class E
Watertightness	Watertight at 10 kPa (method A)
Tensile strength	900 ± 200 N/50 mm (tensile strength longitudinal)
	700 ± 200 N/50 mm (tensile strength transverse)
	50 ± 15 % (elongation longitudinal)
	50 ± 15 % (elongation transverse)
Root resistance	NPD
Resistance to static load	NPD
Resistance to impact	NPD
Resistance to tearing	NPD (nail shank)
Joint strength	NPD (peel resistance of joints)
	NPD (shear resistance of joints)
Durability	NPD
Flexibility	-25 °C (at low temperatures)
Dangerous substances	not contain

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Grzegorz Hese**  
Dyrektor Zakładów  
Produkcji BMI Icopal

At Zduńska Wola on 5th May 2022