

No P035-5

1 Unique identification code of the product-type: **HYDROBIT V60 S42H Szybki Profil SBS**

2 Intended use/es:
 a. roof waterproofing
 b. roof waterproofing subject to reaction to fire

3 Manufacturer:
 BMI Icopal Sp. z o.o., ul. Łaska 169/197,
 98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:
 System 2+, System 3

5 Harmonised standard:
 EN 13707:2004+A2:2009

Notified body/ies:
 The notified factory production control certification body No. 1434:
 POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
 (system 2+, scope of application a.)

The notified testing laboratory No. 1434:
 POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
 (system 3, scope of application b.)

6 Declared performance/s:

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Class E
Watertightness	Watertight
Tensile strength longitudinal	400 ± 100 N/50 mm
Tensile strength transverse	300 ± 100 N/50 mm
Elongation longitudinal	4 ± 2 %
Elongation transverse	4 ± 2 %
Root resistance	NPD
Resistance to static load, method A	NPD
Resistance to impact, method A	NPD
Resistance to tearing	NPD
Peel resistance of joints	NPD
Shear resistance of joints	NPD
Durability: heat flow after heat oven exposure	110 ± 15 °C
Flexibility at low temperatures (pliability)	0 °C
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

CZŁONEK ZARZĄDU
DYREKTOR
DS. TECHNICZNO PRODUKCYJNYCH

Grzegorz Hese

At Zduńska Wola on 20th February 2020