

No **P044-4**

1 Unique identification code of the product-type: **Icopal P Base 30 Speed Profile SBS**

2 Intended use/es: roof waterproofing

3 Manufacturer: BMI Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP: System 2+, System 4

5 Harmonised standard: EN 13707:2004+A2:2009

Notified body/ies: The notified factory production control certification body No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+)

6 Declared performance/s:

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	NPD
Watertightness	Watertight
Tensile strength longitudinal	550 ± 150 N/50 mm
Tensile strength transverse	450 ± 150 N/50 mm
Elongation longitudinal	40 ± 10 %
Elongation transverse	40 ± 10 %
Root resistance	NPD
Resistance to static load, method B	5 kg
Resistance to impact, method A	400 mm
Resistance to impact method B	NPD
Resistance to tearing longitudinal	200 ± 100 N
Resistance to tearing transverse	200 ± 100 N
Peel resistance of joints	NPD
Shear resistance of joints, side lap	450 ± 150 N/50 mm
Shear resistance of joints, end lap	550 ± 150 N/50 mm
Durability: heat flow after heat oven exposure	NPD
Durability: flexibility at low temperature after heat oven exposure	NPD
Flexibility at low temperatures (pliability)	-10 °C
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 20th February 2020

CZŁONEK ZARZĄDU
 DYREKTOR
 DS. TECHNICZNO PRODUKCYJNYCH

Grzegorz Hase