

No **P045-5**

- 1 Unique identification code of the product-type:** **Icopal P Base 30 Speed Profile SBS - typ T**
- 2 Intended use/es:** damp proofing for buildings, including basement tanking
- 3 Manufacturer:** BMI Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)
- 4 System/s of AVCP:** System 2+, System 4
- 5 Harmonised standard:** EN 13969:2004, EN 13969:2004/A1:2006
- Notified body/ies:** The notified factory production control certification body No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+)
- 6 Declared performance/s:**

Essential characteristics	Performances
Reaction to fire	NPD
Watertightness	Watertight
Resistance to impact, method A	400 mm
Resistance to impact, method B	NPD
Shear resistance of joints, side lap	450 ± 150 N/50 mm
Shear resistance of joints, end lap	550 ± 150 N/50 mm
Flexibility at low temperatures (pliability)	-10 °C
Tensile strength longitudinal	550 ± 150 N/50 mm
Tensile strength transverse	450 ± 150 N/50 mm
Elongation longitudinal	40 ± 10 %
Elongation transverse	40 ± 10 %
Resistance to static load, method B	5 kg
Resistance to tearing longitudinal	200 ± 100 N
Resistance to tearing transverse	200 ± 100 N
Durability against artificial ageing/degradation: watertightness	Watertight
Durability against chemicals: watertightness	NPD
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 12th October 2020


Grzegorz Hese
 Dyrektor Zakładów
 Produkcji BMI Icopal