

No **P046-4**

**1 Unique identification code of the product-type:** **Icopal PA Top 40 Speed Profile SBS**

**2 Intended use/es:** roof waterproofing

**3 Manufacturer:** BMI Icopal Sp. z o.o., ul. Łaska 169/197,  
98-220 Zduńska Wola, Polska (PL)

**4 System/s of AVCP:** System 2+, System 4

**5 Harmonised standard:** EN 13707:2004+A2:2009

**Notified body/ies:** The notified factory production control certification body No. 1434:  
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.  
(system 2+)


**6 Declared performance/s:**

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	NPD
Watertightness	Watertight
Tensile strength longitudinal	550 ± 150 N/50 mm
Tensile strength transverse	450 ± 150 N/50 mm
Elongation longitudinal	40 ± 10 %
Elongation transverse	40 ± 10 %
Root resistance	NPD
Resistance to static load, method A	NPD
Resistance to impact, method A	NPD
Resistance to tearing	NPD
Peel resistance of joints	NPD
Shear resistance of joints	NPD
Durability: heat flow after heat oven exposure	110 ± 15 °C
Flexibility at low temperatures (pliability)	-10 °C
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

  
 CZŁONKARZ DPU  
 DYREKTOR  
 DS. TECHNICZNO PRODUKCYJNYCH  
 Gregorz Hase

At Zduńska Wola on 20th February 2020