

No P055-8

- 1 Unique identification code of the product-type:** **Fundament Antyradon 4,0 Szybki Profil SBS**
- 2 Intended use/es:** damp proofing for buildings, including basement tanking
- 3 Manufacturer:** BMI Icopal Sp. z o.o., ul. Łaska 169/197, 98-220 Zduńska Wola, Polska (PL)
- 4 System/s of AVCP:** System 2+, System 4
- 5 Harmonised standard:** EN 13969:2004, EN 13969:2004/A1:2006
- Notified body/ies:** The notified factory production control certification body No. 1488: INSTYTUT TECHNIKI BUDOWLANEJ (system 2+)

6 Declared performance/s:

Essential characteristics	Performances
Reaction to fire	NPD
Watertightness	200 kPa
Impact resistance	1500 mm (method A)
	2000 mm (method B)
Joint strength	800 +200/-100 N/50 mm (shear resistance of joints, side lap)
	1000 +200/-100 N/50 mm (shear resistance of joints, end lap)
Low temperature flexibility	-12 °C
Tensile strength	950 +350/-0 N/50mm (tensile strength longitudinal)
	750 +350/-0 N/50mm (tensile strength transverse)
	50 ± 15 % (elongation longitudinal)
	50 ± 20 % (elongation transverse)
Resistance to static loading	20 kg (method B)
Resistance to tearing	350 ± 100 N (nail shank, longitudinal)
	350 ± 100 N (nail shank, transverse)
Durability	200 kPa (watertightness after artificial ageing)
	NPD (chemical resistance, watertightness)
Dangerous substances	Not contain

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 12th October 2020

Grzegorz Hese

Dyrektor Zakładów
Produkcji BMI Icopal