

No P067-6

1 Unique identification code of the product-type: **Junior Top 4,2 Szybki Profil SBS**

2 Intended use/es:

- a. roof waterproofing
- b. roof waterproofing subject to reaction to fire

3 Manufacturer:

BMI Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:

System 2+, System 3

5 Harmonised standard:

EN 13707:2004+A2:2009

Notified body/ies:

The notified factory production control certification body No. 1488:
INSTYTUT TECHNIKI BUDOWLANEJ
(system 2+, scope of application a.)

The notified testing laboratory No. 1486:
CENTRALNY OŚRODEK BADAWCZO – ROZWOJOWY
PRZEMYSŁU IZOLACJI BUDOWLANEJ
(system 3, scope of application b.)

6 Declared performance/s:

Essential characteristics	Performances
External fire performance	NPD*
Reaction to fire	Class E
Watertightness	Watertight
Tensile strength longitudinal	550 +300/-0 N/50 mm
Tensile strength transverse	300 +250/-0 N/50 mm
Elongation longitudinal	5 ± 3 %
Elongation transverse	5 ± 3 %
Root resistance	NPD
Resistance to static load, method A	NPD
Resistance to impact, method A	NPD
Resistance to tearing	NPD
Peel resistance of joints	NPD
Shear resistance of joints	NPD
Durability: flexibility at low temperature after heat oven exposure	-20 ± 5 °C
Flexibility at low temperatures (pliability)	-25 °C
Dangerous substances	not contain

NPD - No performance determined

* Phrase NPD results from the impossibility of determining the performance of this product.

The performance is determined as B_{ROOF} (t1) for specific roofing systems including this product (available on the ICOPAL website).

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

CZŁONEK ZARZĄDU
DYREKTOR
DS. TECHNICZNO PRODUKCYJNYCH

At Zduńska Wola on 4th March 2020

Grzegorz Hase