

No P151-1

1 Unique identification code of the product-type: **W/PET PLUS - SBS/ICOPAL**

2 Intended use/es:
 a. roof waterproofing
 b. roof waterproofing subject to reaction to fire

3 Manufacturer: BMI Icopal Sp. z o.o., ul. Łaska 169/197,
 98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP: System 2+, System 3

5 Harmonised standard: EN 13707:2004+A2:2009

Notified body/ies:

The notified factory production control certification body No. 1434:
 POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
 (system 2+, scope of application a.)


The notified testing laboratory No. 1434:
 POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
 (system 3, scope of application b.)

6 Declared performance/s:

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Class E
Watertightness	Watertight at 10 kPa (method A)
Tensile properties	450 ± 150 N/50 mm (tensile strength longitudinal)
	350 ± 150 N/50 mm (tensile strength transverse)
	30 ± 15 % (elongation longitudinal)
	35 ± 15 % (elongation transverse)
Root resistance	NPD
Resistance to static loading	NPD
Resistance to impact	NPD
Tear resistance	250 ± 100 N (nail shank, longitudinal)
	250 ± 100 N (nail shank, transverse)
Joint strength	NPD (peel resistance of joints)
	NPD (shear resistance of joints)
Durability	115 ± 15 °C (heat flow after heat oven exposure)
Pliability	-10 °C (flexibility at low temperature)
Dangerous substances	Not contain

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Grzegorz Hiesc
 Dyrektor Zakładów
 Produkcji BMI Icopal

At Zduńska Wola on 23rd October 2020