

No **P152**

1 Unique identification code of the product-type:

**ICOPAL TOP EXTRA PYE PV250 S53
SZYBKI PROFIL SBS**

2 Intended use/es:

- a. roof waterproofing
- b. roof waterproofing subject to reaction to fire

3 Manufacturer:

BMI Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:

System 2+, System 3

5 Harmonised standard:

EN 13707:2004+A2:2009

Notified body/ies:

The notified factory production control certification body No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+, scope of application a.)

The notified testing laboratory No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 3, scope of application b.)


6 Declared performance/s:

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Class E
Watertightness	Watertight at 10 kPa
Tensile strength longitudinal	1000 ± 300 N/50 mm
Tensile strength transverse	800 ± 300 N/50 mm
Elongation longitudinal	50 ± 15 %
Elongation transverse	50 ± 15 %
Root resistance	NPD
Resistance to static load, method A	20 kg
Resistance to impact, method A	1000 mm
Resistance to impact, method B	1500 mm
Resistance to tearing	NPD
Peel resistance of joints	NPD
Shear resistance of joints, side lap	800 ± 300 N/50 mm
Shear resistance of joints, end lap	1000 ± 300 N/50 mm
Durability: flexibility at low temperature after heat oven exposure	-20 ± 5 °C
Flexibility at low temperatures (pliability)	-25 °C

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Grzegorz Hese
 Dyrektor Zakładów
 Produkcji BMI Icopal

At Zduńska Wola on 17th August 2021