

No **P153**

1 Unique identification code of the product-type: **GLASBIT G200 S40-15 SZYBKI PROFIL SBS**

2 Intended use/es:
 a. roof waterproofing
 b. roof waterproofing subject to reaction to fire

3 Manufacturer: BMI Icopal Sp. z o.o., ul. Łaska 169/197,
 98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP: System 2+, System 3

5 Harmonised standard: EN 13707:2004+A2:2009

Notified body/ies: The notified factory production control certification body No. 1434:
 POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+, scope of application a.)

The notified testing laboratory No. 1434:
 POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 3, scope of application b.)

6 Declared performance/s:


Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Class E
Watertightness, method A	Watertight at 10 kPa
Tensile strength longitudinal	1500 ± 500 N/50 mm
Tensile strength transverse	2500 ± 700 N/50 mm
Elongation longitudinal	8 ± 5 %
Elongation transverse	8 ± 5 %
Root resistance	NPD
Resistance to static load, method B	10 kg
Resistance to impact, method A	2000 mm
Resistance to impact, method B	NPD
Resistance to tearing longitudinal	500 ± 250 N/50 mm
Resistance to tearing transverse	250 ± 100 N/50 mm
Peel resistance of joints	NPD
Shear resistance of joints, side lap	1500 ± 1000 N/50 mm
Shear resistance of joints, end lap	1500 ± 1000 N/50 mm
Durability: heat flow after heat oven exposure	NPD
Durability: flexibility at low temperature after heat oven exposure	NPD
Flexibility at low temperatures (pliability)	-15 °C

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 17th August 2021


Grzegorz Hese
 Dyrektor Zakładów
 Produkcji BMI Icopal